

1. PRODUCT NAME

Color Caulk Sanded / UnSanded

2. MANUFACTURER

PROFLEX® Products, Inc.
1603 Grove Ave
Haines City, FL 33844
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us



3. PRODUCT DESCRIPTION

Premium Acrylic Caulk is a high performance siliconized acrylic latex sealant designed for interior and exterior applications for ceramic tile and stone. Premium Acrylic Caulk is ideal for a variety of caulking applications in bathrooms, kitchens and floors.

Uses

- For caulking around sinks, tubs and showers
- Great for sealing joints between countertop and backsplashes
- Corner joints where walls meet
- Sealing fixtures
- Control Joints where surface abrasion is limited

Suitable Surfaces

- Ceramic Tile
- Marble
- Glass Block
- Porcelain
- Stone*
- Fiberglass

* Conduct small test area to verify if any staining occurs. Discontinue use if any migration is evident

Advantages

- Resists mold & mildew growth.
- Stain resistant
- Matches PROFLEX® grout colors
- Easy to smooth and tool
- Adheres well to plumbing fixtures
- Resistant to staining and cracking
- Flexible
- Suitable for interior and exterior applications

Limitations

- Not for submerged and or permanent wet area applications
- Sealants are not replacements for waterproofing membranes. When a waterproofing membrane is required, use PROFLEX® Waterproofing Membranes
- For sensitive porous substrates such as limestone and sandstone, test sealant on a small area for any indication of fluid migration prior to job commencement.
- Not for joint applications where physical abuse or abrasion is likely
- Not a structural glazing adhesive.
- Joint width should not exceed 1/4" (6.0 mm) thickness and no thinner than 1/8" (3.2 mm).
- Where sealant depth is more than 2 times the joint width, backer rod is recommended

Coverage

Coverage will vary depending upon joint size and width.
Approximately 25 lineal feet (7.62 m) per tube at 1/4" x 1/4" (6 x 6 mm) joint width.

Packaging

10.5 oz (310 ml) tubes.
12 tubes per carton

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for (2) years if stored at temperatures between 32°F (0°C) and 110°F (43°C).

4. TECHNICAL DATA

Physical Properties

Service Temperature Range	Unsanded -20°F (-28°C) to 180°F (82°C) Sanded 0°F (-17°C) to 180°F (82°C)
Application Temperature Range	40°F (4°C)–105°F (40°C)
Open Time	10–20 Minutes
Set Time	72 Hours
Full Cure	2 Weeks
Clean Up	Soapy Water
Mildew Resistance	Good
Consistency	Non-sag

Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Clean all joints and glazing pockets, removing all foreign matter and contaminants such as grease, oil, dust, water, frost, surface dirt, old sealants and protective coatings. In all cases where utilized, solvents should be wiped on and off with clean, oil and lint free cloths. When using any cleaning solvent always follow solvent manufacturer's safety and handling recommendations. For stone, or agglomerate tile test small area to check for any fluid migration.

Application

Apply masking tape to the face or surface to protect it from the sealant. Masking tape will allow for easier removal of sealant if any comes into contact with the face of the tile. Sealant should only be applied into the joints, adhering on the sides of surfaces. Applying the masking tape results in a cleaner look and allows for easy tooling without spillage onto the face of the surfaces. Use backer rod where depth exceeds 2 times joint width. Apply sealant to the joint, filling completely. Tool when complete (within 5–7 minutes) for a smooth professional finish. Remove masking tape immediately after tooling. Wipe any sealant off the face of the stone immediately. Allow 72 hours for curing. A second application may be necessary. Allow 24 hours between applications.

Cleaning

Wipe any sealant off the face of the stone immediately.

6. AVAILABILITY

PROFLEX® Products are available nationwide.

To locate PROFLEX® products in your area, please contact:

Phone: 877-577-6353

Website: www.proflex.us

7. WARRANTY

PROFLEX® Products, Inc. offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical services at 877-577-6353 or visiting www.proflex.us

8. MAINTENANCE

Joints should be cleaned regularly with common cleaners on a regular basis..

9. TECHNICAL SERVICES

Technical assistance

Information is available by calling the Technical Support

Toll Free: 877-577-6353

Fax: 863-937-9624

Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9