

1. PRODUCT NAME

Rebond-It™

2. MANUFACTURER

PROFLEX® Products, Inc.
1603 Grove Ave
Haines City, FL 33844
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us

3. PRODUCT DESCRIPTION

PROFLEX® ReBond-It™ is an easy to use bonding compound designed to rebond loose or hollow tiles without the costly expense of replacing them. The compound is safe, easy to install, and easy to clean. Used by tile professionals and builders to provide an economical alternative to removing and resetting tiles.



Advantages

- Dries in as little as 10 hours
- Easy Clean-up
- Bonds to most surfaces

Rebond loose or hollow flooring from a variety of surfaces including:

- Ceramic Tile
- Quarry Tile
- Porcelain Tile
- Stone
- Marble
- Engineered Hardwood

Product Limitations

Do not freeze product. Use only in temperatures above 42° F. Additional applications may be necessary to achieve desired results. Even then, complete coverage may not be achieved. Do not use in showers, pools, or areas where moisture is present.

Caution

Eye and skin irritant. Promptly wash eyes with water for 15 minutes. Consult physician if irritation persists. Skin contact should be washed with soap and water. If inhaled, get to fresh air immediately. If ingested, drink several glasses of water immediately, and call a physician or poison control center.

Available in

10 oz / 296 ML Tube - 12 per Carton
30 oz / 887 ML Tube - 12 per Carton



4. TECHNICAL DATA

N/A

5. INSTALLATION

1. Identify the tile(s) that will need to be rebonded. (Tap the surface of a tile, hollow sounding tiles will be in need of repair.)
2. Using a masonry bit, bore holes in 6 places in the grout surrounding each loose or hollow tile needing repair. (Be sure to use a bit slightly smaller than the grout joint.) Additional penetrations may be required. Clear loose debris from the holes thoroughly. This can be accomplished by forcing air from the holes by tapping the surface with a rubber mallet or by using a vacuum on the penetrations.
3. Fill ReBond-It™ into each hole. There may be some initial resistance to filling the penetrations, apply additional, but not excessive, force to continue the fill. While filling the penetrations, tap the surface area with a rubber mallet to monitor the fill of the ReBond-It™. Wipe away excess ReBond-It™ with a wet sponge, and follow with a dry sponge. Place a weight (25-30 lbs.) on each repaired surface for a minimum of 10 hours to allow ReBond-It™ to activate. Additional time may be necessary. After ReBond-It™ has significantly bonded, remove any excess ReBond-It™ from penetrations with a knife or razor blade. Penetrations may be filled with grout matching original color.

6. AVAILABILITY

PROFLEX® Products are available nationwide.

To locate PROFLEX® products in your area, please contact:

Phone: 877-577-6353

Website: www.proflex.us

7. WARRANTY

Since the specific use of this product is beyond the control of the seller, liability of the seller will be limited to the replacement cost of this product only for six months after the date of purchase.

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Information is available by calling the Technical Support

Toll Free: 877-577-6353

Fax: 863-937-9624

Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9