

1. PRODUCT NAME

UAR (Urethane Adhesive Remover)

2. MANUFACTURER

PROFLEX® Products, Inc.
1603 Grove Ave
Haines City, FL 33844
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us

3. PRODUCT DESCRIPTION

PROFLEX® UAR is a superior, highly refined solvent formulation designed for cleaning up uncured urethane adhesives from prefinished wood flooring and other surfaces.

Advantages

- Removes uncured urethane from wood flooring surfaces
- Cleans tools
- No odor
- Formulated for professionals

Packaging

32 OZ (1 QT) packed, 6 per case

Cautions and Limitations

Remove excess adhesive before it cures. UAR will not remove cured adhesive. Use a clean, soft cloth that will not damage the floor. Do not allow UAR to run into the joints of the flooring during application.

Avoid contact with eyes and prolonged contact with skin.

For professional use only.

Not for sale or use in California.

Safety Data

DANGER! HARMFUL OR FATAL IF SWALLOWED.

EYE IRRITANT. COMBUSTIBLE.

Contains Petroleum Distillates.

Keep away from heat, sparks, open flames, and other ignition sources.

Wear goggles and gloves. If the work area is not well ventilated, do not use UAR.

FIRST AID - IF SWALLOWED, do not induce vomiting. Immediately call poison control center or hospital emergency room.

IN CASE OF EYE CONTACT, immediately flush with water for at least 15 minutes, then get medical attention.

IN CASE OF PROLONGED SKIN CONTACT, wash thoroughly with soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN.

Storage

Do not use or store UAR near sources of heat or open flame, furnaces, pilot lights, stoves, etc. Store UAR in a cool dry place, out of direct sunlight, at temperatures below 90°F as high temperatures or prolonged exposure to sun may cause container to swell or leak. Keep container closed when not in use.

4. TECHNICAL DATA

Physical State: Liquid

Color: Clear

Flash point: 118°F – TAG Closed Cup

VOC 782 g/L



The logo for UAR consists of the letters "UAR" in a large, white, bold, sans-serif font, centered within a dark blue rectangular background.

2 of 2

Specific Gravity 0.76 @ 15.6°C (60.1°F)
Shelf Life: 12 months in an unopened container

5. INSTALLATION

FOR USE AS A SURFACE CLEANER

1. Apply UAR to a clean, soft cloth.
2. Gently wipe clean, the affected area, applying more UAR to the cloth when necessary. Use another clean cloth and repeat if needed.
3. After the adhesive has been removed, wipe off any residue with a dry clean cloth.

FOR USE AS A TOOL CLEANER:

1. Apply UAR to a clean cloth or soak the tool with UAR.
2. Wipe or scrape the adhesive from the tool.

6. AVAILABILITY

PROFLEX® Products are available nationwide.
To locate PROFLEX® products in your area, please contact:
Phone: 877-577-6353
Website: www.proflex.us

7. WARRANTY

UAR is warranted to be free of manufacturing defects for a period of one year from the date of manufacture. Any product found to be defective by PROFLEX® Products, Inc. will be replaced or the purchase price refunded. Suitability of UAR for an intended use shall be entirely up to the user. PROFLEX® Products, Inc. assumes no responsibility for personal injury or property damage since the conditions under which UAR is transported, stored, sold, used or applied is beyond our control. No other warranties are expressed or implied.

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical assistance
Information is available by calling the Technical Support
Toll Free: 877-577-6353
Fax: 863-937-9624
Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9