

1. PRODUCT NAME

Max Floor Cleaner

2. MANUFACTURER

PROFLEX® Products, Inc.
1603 Grove Ave.
Haines City, FL 33844
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us

3. PRODUCT DESCRIPTION

Max Floor Cleaner is a heavy duty pro-grade cleaner that removes efflorescence, hard water build-up, lime and rust stains. A safe water based cleaner for all interior and exterior surfaces. Great for grout and porous surfaces.



Advantages

- Deep cleaning with minimal effort on grout, tile, natural and fabricated stone, polished stone
- Contains a biocide that kills and removes mold and mildew
- Environmentally friendly, no CFC's
- Safe for everyday cleaning on most surfaces
- Non-Toxic, V.O.C. compliant (less than 62 g/l)
- Non-Flammable - Flash Point > 200°F

Usage

Household uses: Very effective on grout, glazed and unglazed tile, natural and fabricated stone, polished stone, terracotta, adobe tile, resilient tile, masonry and many, many other surfaces. Will remove dirt, grime and stains from surfaces especially grout and porous stone. Will remove grime, greases and oils, and a wide variety of other organic compounds. Max Floor Cleaner is safe on most surfaces but always test in an inconspicuous area to determine suitability.

Test application should be performed especially on painted surfaces.

Packaging

1 Gal (PS57)

Coverage

Max Floor Cleaner, when diluted, provides 64 up to 128 gallons of cleaning mixture. Coverage is approximately 10,000 to 20,000 sq. ft. per gallon.

WARNINGS

Protect from freezing. May affect soundness of some paints. Skin contact should be minimized by wearing gloves, appropriate clothing, and eye protection. Protect all non-targeted adjacent surfaces, window glass, vehicles, aluminum, paint films and plant life. Remove overspray immediately with water. Use in a well-ventilated area.

4. TECHNICAL DATA

n/a

5. INSTALLATION

Application: (Read entire label before using)

Shake well. For best results vacuum or sweep surface to be cleaned, making sure to remove all loose debris.

1. Mix 1 to 4 ounces of Max Floor Cleaner per gallon of water (for best results warm water is recommended).
2. On polished natural stone 1 to 2 ounces per gallon is generally very effective.
3. Spread the solution over the area to be cleaned and allow to stand for 2 to 3 minutes.
4. Agitate with a soft bristle brush or a mop concentrating heavily soiled areas.
5. Mop up dirty solution.

Solution should be changed a minimum of 250 sq. ft. or as needed.

6. AVAILABILITY

PROFLEX® Products are available nationwide.

To locate PROFLEX® products in your area, please contact:

Phone: 877-577-6353

Website: www.proflex.us

7. WARRANTY

Limited Lifetime

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Information is available by calling Technical Support.

Toll Free: 877-577-6353

Fax: 863-937-9624

Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9