PROFLEX®

ENHANCING SEALER

04.17.24

1. PRODUCT NAME

Enhancing Sealer



2. MANUFACTURER

PROFLEX® Products, Inc.
1603 Grove Ave.
Haines City, FL 33122
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us

3. PRODUCT DESCRIPTION

Pro Seal Enhancer is an excellent solvent based sealer formulated to protect and highlight the character and beauty of unsealed natural marble. It rejuvenates the color and improves the appearance of worn and weathered marble. An invisible barrier is formed that resists water, grease, oil, stains, and dirt. Allows moisture-vapor transmission so the surface remains breathable.

Test a small area. Do so according to application instructions with a 24-hour cure time to determine the desired results.
Test for stain repellency using likely contaminants.

Advantages

- Interior or Exterior Use
- Seals and Enhances in 1 application
- Deep and rich color enhancement
- Low VOC (less than 100 g/l)
- Excellent water and stain repellency
- Deep Penetration
- 15 Year Protection

Usage

Use on unsealed marble, granite, travertine, unglazed tile, fabricated stone, and tumble stone. Effective for interior and exterior applications. Works on most porous architectural substrates.

Packaging

1 Gal (PS66GA), 32 oz (PS66QT), 16 oz (PS66PT)

Coverage

Coverage is 500 to 1500 sq. ft. per gallon per coat, but will vary depending on type of stone, porosity and texture of surface absorption, temperature, humidity, and method of application.

Limitations

Do not allow sealer to come in contact with any non-recommended surface as product is not completely removable. Sealers and finishes should not be used before or after use of Pro Seal Enhancer. **If Pro Seal Enhancer is not WIPED COMPLETELY DRY within 5minutes, a residue may form**. If residue occurs, use a scrub brush with alcohol to remove. Keep floor surfaces dry and clean to reduce the possibility of slip-fall accidents. Routine pressure washing will affect expected wear. Sealer will not prevent surface wear or washing from acids or caustic chemicals.

Expected Wear

04.17.24

Will vary from application to application, and is affected by a number of factors including surface texture and hardness, traffic and surface wear, and weather conditions (exterior applications) but can be expected to last up to 15 years on interior applications and up to 7 years on exterior applications.

WARNING

Keep out of reach of children. Once enhanced, surface cannot be restored to original color appearance. Use in well-ventilated areas. Avoid prolonged skin contact. Rubber gloves and eye protection should be worn during application.

First Aid

If ingested: if person is conscious, immediately give 2 glasses of water and do not induce vomiting. Seek medical attention.
Eye contact: Flush with water. If irritation persists, seek medical attention.
Skin contact: Wash immediately with soap and water. If irritation persists seek medical attention.
Inhalation: Relocate to fresh air. If symptoms persist, seek medical attention.

4. TECHNICAL DATA

n/a

5. INSTALLATION

Application

1. Read entire label before using.
2. Surfaces must be clean, dry, and free of existing sealers or coatings.
3. Apply using a sponge, paint pad, or cotton towel. ***NOTE: Be sure that any sealer that does not penetrate surface is polished dry off surface within 5 minutes of application using absorbent paper or cotton towels.***
4. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats.
5. Ready for surface traffic in 12-hour safter final coat. Keep dry for 12 hours. Achieves full cure in 48 hours. Some highly porous surfaces may require an additional coat after full cure.
6. Clean applicator tools with mineral spirits after each use.

6. AVAILABILITY

PROFLEX® Products are available nationwide.
To locate PROFLEX® products in your area, please contact:
Phone: 877-577-6353
Website: www.proflex.us

7. WARRANTY

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.

04.17.24

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical assistance
Information is available by calling the Technical Support
Toll Free: 877-577-6353
Fax: 863-937-9624
Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9