PROFLEX®

PFP Shield

JAN 2026

1. PRODUCT NAME

PFP Shield

2. MANUFACTURER

PROFLEX® Products, Inc.
1603 Grove Ave.
Haines City, FL 33122
Telephone: 863-937-9623
Toll Free: 877-577-6353
Fax: 863-937-9624
Internet: www.proflex.us

3. PRODUCT DESCRIPTION

PROFLEX® PFP Shield offers a variety of surface protection products from damage, moisture, or other in-construction related hazards. PFP Shield defends against water, paint, mud, and more. All of our PFP Shield line of products are made from 100%recycled materials from both post-industrial and post-consumer products, and are eligible to be used to contribute to LEED certification.

Uses

Protects Granite, Travertine, Marble, Terrazzo, Stone, Colored Concrete, Tile, Wood, Carpet, Linoleum, etc. Excellent protection for floors, walls, countertops, cabinets, and more.

Advantages

- 100% recycled product - can be submitted for LEED projects.
- Installs quickly and lays flat to finish surface.
- PRO-SHIELD defends against water, paint, mud and more.
- Heavy-duty, water resistant temporary floor protection.
- Tough enough to be driven on

Packaging

PFP Shield is available in a 38” x 100’ roll, 46 lbs.

4. TECHNICAL DATA

Physical Properties

Thickness		44 mil Ø
Density		3.26 - 3.31
Mullen Burst		140 psi
Taber Stiffness MD		1703.7 gf/cm

JAN 2026

Taber Stiffness CD Caliper		647.6 gf/cm

Low Spec: 44.01 Basis Weight	Target Spec: 45.03	High Spec: 46.02
Low Spec: 140.90 Moisture	Target Spec: 143.97	147.05
Low Spec: 4.05%	Target Spec: 6.0%	High Spec: 7.5%

5. INSTALLATION

Instructions

Remove plastic sleeve. Place on desired surface and unroll. Cut to length with a utility knife. Seam multiple pieces together with masking tape for larger areas.

6. AVAILABILITY

PROFLEX® Products are available nationwide.
To locate PROFLEX® products in your area, please contact:
Phone: 877-577-6353
Website: www.proflex.us

7. WARRANTY

N/A

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers. Keep away from flammable and combustible material. Paper products will not release hazardous chemicals under normal conditions of use.

9. TECHNICAL SERVICES

Technical assistance
Information is available by calling the Technical Support
Toll Free: 877-577-6353
Fax: 863-937-9624
Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9